


UNI-T

Uni-Trend Your Testing Specialist!








Certificate No.: QAC0956661








ANBI
www.anbisolutions.com




UNI-T Test and Measuring Instruments list





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
1	A12T	A12T(CE) UNI-T Portable Mini Temperature & Humidity Meter - Indoor/Outdoor	6935750512272	80	
2	A13T	A13T UNI-T Portable Mini Temperature & Humidity Meter, Time-Alarm-Date & Calendar - Indoor	6935750513293	80	
3	A61	A61 UNI-T Digital pen type thermometer - 40°C~250°C (-40°F~482°F)	6935750561065	40	
4	UT330B	UT330B UNI-T USB Datalogger (60000 sets data storage, PC software, Trend capture to BMP/CSV/TXT files, High/low temperature alarm, customizable user settings)	6935750533055		
5	UT300S	UT300S UNI-T Non-Contact infrared Digital IR Thermometer (-32C - 400C)	6935750530085	20	
6	UT301A+	UT301A+ UNI-T Non-Contact infrared Digital IR Professional Thermometer (-32°C~420°C)	6935750530177	20	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
7	UT301D+	UT301D+ UNI-T Non-Contact infrared IR Professional Thermometer (-32C to 600C) with 99 Data storage and Scheduled measurement	6935750573013	20	
8	UT309A	UT309A UNI-T Non-Contact Infrared IR Professional Thermometer (-35C - 450C)	6935750530917	10	
9	UT309C	UT309C UNI-T Non-Contact Infrared IR Professional Thermometer (-35°C~650°C)	6935750530931	10	
10	UT302D+	UT302D+ UNI-T Non Contact Infrared IR Professional Thermometer, 20:1 D:S ratio (-32C ~ 1100C)	6935750530290	10	
11	UT303C+	UT303C+ UNI-T Infrared thermometer (-30C to 1300C) (20:1 D:S ratio, Adjustable emissivity 0.1~1.0, ±1.5°C temperature measurement accuracy, User defined visual and audio alarm, High contrast EBTN color display, MAX/MIN/AVG/DIFF/Hold modes)	6935750530375	10	
12	UT302A+	UT302A+ UNI-T Non-Contact infrared IR Professional Thermometer (-32C to 700C) with 20:1 D:S ratio and High contrast EBTN color display	6935750530276	20	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
13	UT303D+	UT303D+ UNI-T Non-Contact infrared IR Professional Thermometer (-32C to 1300C) with 20:1 D:S ratio, High contrast EBTN color display and 99 Data storage with date and time	6935750530399	20	
14	UT30H	UT30H UNI-T Non-Contact Forehead Infrared Thermometer to detect a fever (32C~45C (89.6F~113F))	6935750543153	20	
15	UT306S	UT306S UNI-T Non Contact Infrared Thermometer, robust and easy to use. Wide temperature range - 50 to 500C, EBTN display, Auto power off, Low battery indication, Single Laser., DS:12:1	6935750543382	20	
16	UT306C	UT306C UNI-T Non Contact Infrared Thermometer, robust and easy to use. Wide temperature range - 50 to 500C, EBTN display, Auto power off, Low battery indication, Circle Laser., DS:12:1	6935750530634	20	
17	UTi220B	UTi220B UNI-T Thermal Imager, Excellent infrared resolution and real-time image transmission, 2.8" TFT screen, Infrared resolution: 200 x 150, Temperature measurement range: -10C to 400C , Photograph function with SD card storage, PC analysis software, Buzzer/flashlight alarm, Auto capture of Hi/Low temperature, Flashlight, 1/4" tripod mounting hole, IP65/2m drop proof etc..	6935750502273	10	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
18	UTi260B	UTi260B UNI-T Thermal Imager, Temp Range: -15 to 550C, IR 256x192 pixel, Focus free, Display modes: Thermal, blending, visible and PIP, ROI (eliminates interference), Micro SD card, Type-C USB cable, PC analysis software, Buzzer/flashlight alarm, Real-time image transmission, Auto capture of Hi/Low temperature and IP65/2m drop proof etc.	6935750526149	10	
19	UTi120T	UTi120T UNI-T Thermal Imager, compact design philosophy. pocket type, digital camera, image fusion, Focus free, WiFi, PC analysis software, touch screen, internal storage etc. Infrared resolution: 120x90 Temperature -20C to 400C, Auto tracking for Lo/Hi temperature, Digital zoom, IP54 and 1M Drop proof,		5	
20	UT320D	UT320D UNI-T double channel contact type thermometer, wide temperature range. Calculate the temperature difference of its two channels. used with any K or J temperature probe. 1m drop proof, 4 times/s sampling rate, Max/Min, Average, Data hold, LCD backlight, K type -50C to 1300C and J type -50C to 1200C	6935750532041	20	
21	UT325	UT325 UNI-T Contact Type Thermometer, fast, accurate, and precise temperature measurement with thermocouple temperature probes. Users can select single or dual input, record, and analyze data through PC software and also with a variety of temperature probes (Type K, J, T, E, R, S, N) with Auto calibration.	6935750532508	10	
22	UT333	UT333 UNI-T Mini Temperature & Humidity Meter with built in sensor (-10 - 60C)	6935750533307	40	






S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
23	UT333S	UT333S UNI-T Mini Temperature & Humidity Meter with separate probe (-10 - 60C)	6935750533321	20	
24	UT333BT	UT333BT UNI-T Mini Temperature & Humidity Meter with built in sensor (-10 - 60C) & Bluetooth (UT333BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store or UNI-T's website by searching 'iENV'.)	6935750533314	40	
25	UT331+	UT331+ UNI-T Digital Temperature Humidity Meter (Datalogger), Humidity, Temperature, Dew point and Wet-bulb Temperature offset settings, Auto record time setup, LCD backlight and USB interface for data and power etc..	6935750533376	20	
26	UT332+	UT332+ UNI-T Digital Temperature Humidity Meter (Datalogger), Humidity, Temperature, Dew point and Wet-bulb Temperature offset settings, Auto record time setup, LCD backlight and USB interface for data and power, 999 Data Storage etc..	6935750533383	20	
27	LM40T	LM40T UNI-T Laser Tape, Range 40M and Tape 5M, One-button operation, Single measurement, Rear measurement reference, Unit conversion, Dual measurement methods, Portable and compact.	6935750540947	20	


S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
28	LM60T	LM60T UNI-T Laser Tape, Range 60M and Tape 5M, One-button operation, Single and continuous measurement, unit conversation, Dual measurement mode, Portable and compact.		20	
29	LM40	LM40 UNI-T Portable Digital Laser Distance Meter. Accurately measure Length, Area & Volume by pressing one button - 40M	6935750540022	60	
30	LM60	LM60 UNI-T Portable Digital Laser Distance Meter. Accurately measure Length, Area & Volume by pressing one button - 60M	6935750560167	60	
31	LM50A	LM50A UNI-T Portable Digital Laser Distance Meter. LM A series are new design to measure the distance precisely. It can measure AREA, VOLUME, ADDITION, SUBTRACTION, etc easily. It can also store 99 groups data - 50M.	6935750550182	40	





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
32	LM70A	LM70A UNI-T Portable Digital Laser Distance Meter. LM A series are new design to measure the distance precisely. It can measure AREA, VOLUME, ADDITION, SUBTRACTION, etc easily. It can also store 99 groups data - 70M.	6935750510490	40	
33	LM100A	LM100A UNI-T Portable Digital Laser Distance Meter. LM A series are new design to measure the distance precisely. It can measure AREA, VOLUME, ADDITION, SUBTRACTION, etc easily. It can also store 99 groups data - 100M.	6935750570098	40	
34	LM120A	LM120A UNI-T Portable Digital Laser Distance Meter. LM A series are new design to measure the distance precisely. It can measure AREA, VOLUME, ADDITION, SUBTRACTION, etc easily. It can also store 99 groups data - 120M.	6935750512623	40	
35	LM320B	LM320B UNI-T Angle Meter to measure the precise angle in a variety of applications, designed with 2/4 sided magnetic bottom, and two-side laser design makes the measurement more accurate and convenient! it can be used in manufacturing, home decoration/DIY, and other fields requiring accurate angle measurements. 1. Relative / absolute Measurement 2. 360°comprehensive measurement 3. Data hold 4. Portable and lightweight 5. Unique laser design.	6935750532256	6	





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
36	LM800	LM800 UNI-T Laser Rangefinder, accurate measurement of height, distance, and angle, Distance range - 5~800yd, 7X optical zoom telescope, Height: 0~300yd, Speed: 0~300km/h (0~186mi/h) and Angle: $\pm 45^{\circ}$	6935750580097	6	
37	LM555LD	LM555LD UNI-T Laser Leveler, locate horizontal line, vertical line, and V-H cross-point accurately. IP54 water proof, Self leveling, Built-in Li-ion battery and Working radius: 20m	6935750555507	4	
38	LM570LD-II	LM570LD-II UNI-T Laser Leveler, Green LD laser, suitable for large or bright work places, Application: horizontal, vertical, cross line projection. Self-leveling mode & manual mode. Type-C DC-in port. Complimentary bracket. 2Green laser line and 10M distance.	6935750557044	20	
39	LM575LD	LM575LD UNI-T Laser Leveler, are equipped with green LD laser, suitable for large or bright work places, Applications: horizontal, vertical, cross line projection for decoration, building construction, home decoration, renovation, furniture installation, flooring, and project layout. Self-leveling mode & manual mode, Outdoor pulse mode, 5200mAh Li-ion battery, Type-C DC-in port, Complimentary bracket, Operating distance 40M, Laser lines 3D 12lines.	6935750557518	4	






S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
40	LM576LD	LM576LD UNI-T Laser Leveler, are equipped with green LD laser, suitable for large or bright work places, Applications: horizontal, vertical, cross line projection for decoration, building construction, home decoration, renovation, furniture installation, flooring, and project layout. Self-leveling mode & manual mode, Outdoor pulse mode, 5200mAh Li-ion battery, Type-C DC-in port, Complimentary bracket, Operating distance 30M, Laser lines 3D 16lines.		4	
41	UT116A	UT116A UNI-T SMD Tester, 36V DC voltage measurement, Resistance, capacitance, continuity, diode, The pen can be rotated by 180°, which is convenient for reading and diode/LED, Zener diode polarity test	6935750511602	60	
42	UT116C	UT116C UNI-T SMD Tester, 6000 count, Resistance 60MΩ, capacitance 100mF, 3.2V Diode, continuity, Battery test Load current = 10mA, The pen can be rotated by 180°, which is convenient for reading and diode/LED, Zener diode polarity test		60	
43	UT07A-UK	UT07A-UK UNI-T Socket Tester with UK plug, to check socket wiring errors	6935750507148	96	
44	UT12D-ROW	UT12D-ROW UNI-T Non-contact AC voltage detector, Auto power off Buzzer, LED indication, AC voltage detection, High voltage mode (90V~1000V) / Low voltage mode (24V~1000V).	6935750512432	40	







S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
45	UT12M-ROW	UT12M-ROW UNI-T Professional AC Voltage Detector. IP67 dust/water resistant. Magnetic solenoid detection to detect magnetic fields. Auto power off, Buzzer, LED indication, AC voltage detection, High(90V-1000V) / Low(24V-1000V) voltage mode etc..	6935750512517	40	
46	UT12E-ROW	UT12E-ROW UNI-T Professional AC Voltage Detector. IP67 dust/water resistant. vibration mode. Auto power off, Buzzer, LED indication, AC voltage detection, High(90V-1000V) / Low(24V-1000V) voltage mode etc..	6935750512449	40	
47	UT22B-EU	UT22B-EU UNI-T AC-DC auto detection voltage tester (6V to 400V, Hz, LED indication, IP54, Input protection, drop test.	6935750522035	40	
48	UT15C	UT15C UNI-T Multifunction Voltage and Continuity Tester-12V to 690V - AC/DC with Display	6935750515037	30	
49	UT18C	UT18C UNI-T Voltage and continuity tester with RCD test-12V to 690 - AC/Dcwith Display	6935750518038	30	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
50	UT18D	UT18D UNI-T Voltage and Continuity Tester with LCD display voltage (V) and frequency (Hz), testing AC/DC voltage, range 6V to 690V, 3-phase voltage, continuity, CAT IV 600V and meets IP65 standard. Phase rotation test, Continuity test with buzzer and LED indication, Flashlight, Buzzer and silent modes available, Auto range, Polarity indication and more..	6935750518045	30	
51	UT118B	UT118B Pen Type Digital Multimeter, Display count: 3000, Auto SCAN and range identify mode, LCD backlight and flashlight, Non-contact voltage detection, 300V AC/DC, Resistance and Capacitance.	6935750511824	80	
52	UT105	UT105 UNI-T Automobile Multimeter, Automobiles diagnostic. RPM, DWELL, and other multimeter functions. Applications include working on fuse, switch, solenoid, relay, charging system, fuel system, engine sensing etc.	6935750510506	20	
53	UT107	UT107 UNI-T Hand held Automotive digital multimeter with Temp., Resistance & Frequency - 100VDC & 750VAC (10A MAX)	6935750510704	40	
54	UT120A	UT120A UNI-T Pocket Type Size Digital Multimeter with Resistance & Frequency-600V and Auto Range	6935750541203	60	







S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
55	UT120C	UT120C UNI-T Pocket size digital multimeter with AC/DC current, capacitance, resistance and frequency - 600V and Auto Range	6935750512036	60	
56	UT123	UT123 UNI-T Pocket-sized Residential Multimeter, 600V AC-DC, Resistance, Temp, 4000 count, Auto Range, NCV and Continuity	6923750511237	60	
57	UT123D	UT123D UNI-T Smart Digital Multimeter, automatically identify AC/DC voltage, resistance, diode, and continuity. With the press of one button, all measurement modes can be manually selected including capacitance. The compact design and EBTN display makes it a great tool for home, DIY, and working in dark environments, True RMS, NCV/Live, Low Battery Indication, Data Hold, Auto Power Off, Acousto-optic indication: NCV / continuity / battery power.	6935750511251	60	
58	UT133A	UT133A UNI-T palm size Auto Range 6000Count Digital Multimeter, intellectual ADC chip, overload alarm as well as electricity protection. High voltage warning, Auto power off (can be disabled), Low power consumption, Fast and accurate capacitance measurement, 2m drop proof, 600V AC-DC, 10A AC-DC, Ohm, Cap, Hz, Temp, Diode, NCV and Continuity	6935750513316	30	





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
59	UT136C+	UT136C+ UNI-T Digital Multimeter Auto Power Off Meter AC DC Voltage Current Ohm Diode Cap Hz of Test Diode Multimeter with Temperature (-40C to 1000 C) 1000 V AC/DC and Auto Range	6935750513668	40	
60	UT139C	UT139C UNI-T True RMS digital multimeter. Auto range, Resistance, Frequency and Temperature (-40 C to 1000 C)	6935750531396	40	
61	UT139S	UT139S UNI-T CAT III 600V Digital Multimeter. LoZ (ACV) for measuring 'ghost' voltage. Its built-in 31-segment analog bar, a better visual representation of measurement results. it is a perfect meter for working in dark environments. True RMS, NCV, Auto/manual ranges selectable, Diode, duty ratio and continuity buzzer and Black EBTN screen etc..	6935750513965	20	
62	UT171A	UT171A UNI-T True RMS digital multimeter with Back light, resistance, capacitance & freq. (1000VDC - 1000VAC) and Auto Range	6935750517147	20	





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
63	UT195DS	UT195DS UNI-T Professional handheld industrial digital multimeter with IP65 and 2m drop proof. Troubleshooting capability, resolution, and precision are improved to find issues related to motor drive, factory equipment maintenance, electrical distribution, and repair etc. Dual display, analogue bar graph, Loz, True RMS, 3 phase motor sequence test, etc.		10	
64	UT33A+	UT33A+ UNI-T Palm Size Digital Multimeter with 2mF capacitance test, 2 meters drop test, precision protection, AC-DC V, AC-DC A, Resistance, Diode, Continuity, Auto Range etc.	6935750533147	60	
65	UT33B+	UT33B+ UNI-T Palm size Redefined digital multimeter (Battery test 1.5V/9V/12V) - 600V (10A Max)	6935750533161	60	
66	UT33C+	UT33C+ UNI-T Palm size Redefined digital multimeter with Temperature-600V (10A MAX)	6935750533178	60	
67	UT33D+	UT33D+ UNI-T Palm size Redefined digital multimeter. Resistance 200M and square output-600V (10A MAX)	6935750533185	60	



S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
68	UT39A+	UT39A+ UNI-T Modern Digital multimeter (Capacitance 10mF)-1000VDC & 750 VAC (10A MAX)	6935750539200	30	
69	UT39C+	UT39C+ UNI-T Modern Digital multimeter (Temperature, Capacitance with Frequency) 1000VDC & 750VAC (10A MAX)	6935750516393	30	
70	UT51	UT51 UNI-T Standard Digital multimeter with resistance (1000VDC & 750VAC)	6935750551004	20	
71	UT61D+	UT61D+ UNI-T 1000V AC-DC True RMS 6000count Digital Multimeter, AC-DC A 20A, Ohm, Cap, Hz, Duty Cycle, Temp, Bandwidth (Hz), LoZ ACV, Peak Hold, Analog bar and USB interface etc..	6935750561072	20	
72	UT890D+	UT890D+ UNI-T 6000count true RMS Digital Industrial and Scientific Multimeter with resistance, capacitance, NCV, Continuity & freq. (1000VDC & 750VAC) (20A)	6935750589106	40	
73	UT890C	UT890C UNI-T 6000count true RMS Digital Industrial and Scientific Multimeter with Temp, resistance, capacitance, NCV, Continuity & freq. (1000VDC & 750VAC) (20A)	6935750589113	40	






S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
74	UT89X	UT89X UNI-T True RMS Digital multimeter; 20A high current, NCV, Transistor HFE, 6000count, capacitance, frequency and temp.	6935750589007	20	
75	UT89XD	UT89XD UNI-T True RMS Digital multimeter; 20A high current, NCV, Transistor HFE, 6000count, capacitance, frequency and LED Test	6935750589090	20	
76	UT89XE	UT89XE UNI-T True RMS Digital multimeter; 1000V AC-DC, 20A AC-DC high current, NCV, 20000count, capacitance, conductance, Ohm, frequency, temp. MAX/MIN, Peak Hold and LPF measurement etc..	6935750589137	20	
77	UT601	UT601 UNI-T Digital Inductance Capacitance Meter (From 20 Ohms to 2000 Mega Ohms)	6935750560105	20	
78	UT603	UT603 UNI-T Digital Inductance Capacitance Meter (From 200 Ohms to 20 Mega Ohms)	6935750560303	20	
79	UT210A	UT210A UNI-T 200A True RMS Digital Mini Clampmeter	6935750512104	40	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
80	UT210D	UT210D UNI-T 200A True RMS Digital Mini Clampmeter with Hz & Temp.	6935750521045	40	
81	UT210C	UT210C UNI-T Mini Digital Clamp Meter, 200A AC, AC-DC V, Ohm, Cap, Temp, Continuity, Auto Range, Diode, NCV, 2000count and True RMS etc.	6935750521038	40	
82	UT210E	UT210E UNI-T Mini Digital Clamp Meter 100A AC-DC, AC-DC V, Ohm, Cap, Continuity, Auto Range, Diode, True RMS, 2000count and NCV etc.	6935750521052	40	
83	UT201+	UT201+ UNI-T True RMS, 4000 counts Digital Clamp Meter 400A with Hz, NCV and continuity test	6935750520161	40	
84	UT202+	UT202+ UNI-T True RMS, 4000 counts Digital Clamp Meter 400A with ACHz, NCV and continuity test and Temp (-40C to 1000C)	6935750520260	40	
85	UT202A+	UT202A+ UNI-T Professional Digital Clamp Meter 600A AC with HZ, Ohm, Cap-60mF, 6000count, Auto Range, True RMS, NCV, Live wire test, Continuity, Diode etc.	6935750520277	40	





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
86	UT203+	UT203+ UNI-T True RMS, 4000 counts, 400A AC/DC Digital Clamp Meter with resistance, capacitance, Hz, NCV and continuity test	6935750520383	40	
87	UT204+	UT204+ UNI-T Digital Clamp Meter, 600A AC-DC, Temp., True RMS, NCV, Live wire test, Continuity test and Hz.	6935750520420	40	
88	UT207B	UT207B UNI-T 1000A AC-DC True RMS Digital Clamp Meter, 6000-count, Auto range, large LCD, true RMS, autoscale memory, and NCV functions. CAT III 1000V/CAT IV 600V, CE/ETL. LoZ mode for eliminating 'ghost' voltage, LPF ACV function for measuring INV and VFD voltage, and inrush current mode for capturing transient current. Flashlight, True RMS/Auto backlight, 1000V AC-DC. Hz, Ohm, Capacitance etc..	6935750562079	10	
89	UT216C	UT216C 600A AC-DC, True RMS Digital Clamp Meter, it is designed for measuring high frequency currents (up to 400Hz), Auto range, 3 times/s sampling rate, Temp, Flashlight, NCV, VFC, low pass filter, Zeroing function, Inrush current, Analog bar graph, 6000count etc.	6935750532164	40	






S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
90	UT219DS	UT219DS UNI-T Professional 600A AC-DC Digital Clamp Meter, True RMS with CAT IV 600V IP54 rating, AC-DC V, LoZ ACV, Ohm, Cap, Hz, Temp, 3-phase motor sequence test, Analogue bar graph, Input impedance etc..	6935750521946	10	
91	UT220	UT220 UNI-T 2000A AC Professional Digital Clamp Meter	6935750522080	10	
92	UT221	UT221 UNI-T 2000A AC-DC Digital Clamp Meter, AC-DC V, Ohm, Hz, 6000count, True RMS, Continuity, Analogue bar graph, Inrush current, Input impedance etc..	6935750502211	10	
93	UT243	UT243 UNI-T 1000A handheld and stable power and harmonics clamp meter, with functions of digital ammeter (True RMS, USB interface etc.)	6935750524305	5	




S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
94	UT251C	UT251C UNI-T High Sensitivity Leakage Current Clamp Meter. AC leakage current, checking leakage current for motor, home appliances and other electrical equipment up to 600A.(4-digit LCD digital display, 10000 display count. Auto range, 2/s sampling rate. Peaks hold. Store 99 sets of data. RS-232 interface. Data hold. Auto power off. Overload indication, low battery indication)	6935750525135	20	
95	UT256B	UT256B UNI-T 200A AC-DC True RMS Digital Fork Meter, safety ratings CAT II 1000V, CAT III 600V, Ohm, Cap, Diode, NCV, 6000count, Auto range, Continuity, Input protection, LCD backlight etc.	6935750525623	20	
96	UT281E	UT281E UNI-T True RMS Flex Clamp, 3000A AC, Dual Display interface (LCD), Long press INRUSH key for 2s to measure inrush current, 0~6MΩ resistance and 20~40kHz frequency measurements, Data hold, backlight, auto power off etc.	6935750528150	10	
97	UT275	UT275 UNI-T Digital Clamp Earth Ground Tester, Earth Ground Resistance 0.01 to 1000Ohm, Leakage current (A) upto 30A, Resistance limit alarm, Auto range, Data recall, Auto calibration and 10000 display count etc.	6935750527504	5	





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
98	UT278A	UT278A UNI-T Digital Clamp Earth Ground Tester, Earth Ground Resistance 0.01 to 1200Ohm, Leakage current (A) upto 30A, 4 digits LCD display, Resistance measurement frequency, 1Second Single measurement time, Current limit alarm, Current measurement frequency, RS232, Visual and audible alarm, Jamming signal recognition, Over range display and Auto range etc.	6935750527818	6	
99	UT261A	UT261A UNI-T Phase sequence and missing phase indicator	6935750526118	20	
100	UT261B	UT261B UNI-T Phase sequence and Motor Rotation indicator	6935750526118	20	
101	UT262C	UT262C UNI-T Non-Contact Phase Detector	6935750532621	10	
102	UT-C02A	UT-C02A UNI-T Insulated Alligator Clips with Banana Jack Length: 80mm Clip Opening: 36mm	6935750513026	120	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
103	UT-C02B	UT-C02B UNI-T insulated Alligator Clips with M4 Screw Connection. Length: 80mm Clip Opening: 36mm	6935750514023	120	
104	UT-C04A	UT-C04A UNI-T Insulated Alligator Clips with Banana Jack Length: 75mm Clip Opening: 27mm	6935750500453	120	
105	UT-L20	UT-L20 UNI-T Test Lead Probe Cable Length: 900mm Rod Length: 101mm Tip Length: 16.5mm CAT-I 1000V / CAT-II 600V-10A	6935750512203	100	
106	UT-L21	UT-L21 UNI-T Test Lead Probe Cable Length: 900mm Rod Length: 133mm Tip Length: 15.8mm CAT-III 1000V / CAT-IV 600V-20A	6935750521120	100	
107	UT-L25	UT-L25 UNI-T Test Lead Probe Cable Length: 900mm Rod Length: 115mm Tip Length: 18mm CAT-III 1000V / CAT-IV 600V-10A Removeable tip shield sleeve	6935750525128	100	
108	UT-C07	UT-C07 UNI-T Multifunctional electric test clips, Specifications: Rod length 110mm, adjustable clip length 8mm, Safety level: CAT III 1000V/CAT IV 600V 5A, Features: Standard transfer socket, adjustable multifunctional clips, Amount: 1 pair	6935750500736	100	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
109	UT-L57A	UT-L57A UNI-T Alligator Clip Test Cable Length of Test Cable: 5 Meter Support UT 521 & UT 522	0	40	
110	UT-L58A	UT-L58A UNI-T Alligator Clip Test Cable Length of Test Cable: 10 Meter Support UT 521 & UT 522	0	40	
111	UT-L59A	UT-L59A UNI-T Alligator Clip Test Cable Length of Test Cable: 20 Meter Support UT 521 & UT 522	0	40	
112	UT-T03	UT-T03 UNI-T Submersed thermocouple, Probe length: 180mm, Lead wire length: 1000mm, Test range: -50C to 600C (58F to 1112F), Features and application: metal covers from head to handle, used for liquid and gel temperature measurement	0	40	






S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
113	UT352	UT352 UNI-T Digital Sound Level Meter with data storage (30 - 130 db)	6935750535202	30	
114	UT353	UT353 UNI-T Mini Digital Sound Level Meter (30 - 130 db)	6935750535301	40	
115	UT353BT	UT353BT UNI-T Mini Digital Sound Level Meter (30 - 130 db) with Bluetooth (UT353BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store or UNI-T's website by searching 'iENV'.)	6935750535318	20	
116	UT362	UT362 UNI-T Digital Anemometer with USB interface	6935750536209	5	
117	UT363	UT363 UNI-T Digital Mini Anemometer	6935750536308	40	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
118	UT363S	UT363S UNI-T Digital Anemometer - split-type, featuring quick detection, low consumption and high accuracy.	6935750536339	20	 The image shows a red and black split-type digital anemometer. It consists of a handheld probe with a fan and a separate display unit connected by a coiled cable. The display shows '0.00' and '29.5'. There are CE and RoHS certification marks in the top left corner.
119	UT363BT	UT363BT UNI-T Digital Mini Anemometer with Bluetooth (UT363BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store or UNI-T's website by searching 'iENV'.)	6935750536315	20	 The image shows a red and black digital mini anemometer. It has a fan at the top and a display on the front showing '12.0' and '25.9'. There are icons for CE, RoHS, Bluetooth, and a mobile app in the top left corner.
120	UT311	UT311 UNI-T Portable LCD Vibration Analyzer Tester Meter (All in One)	6935750531105	5	 The image shows a red and black handheld vibration analyzer. It has a digital display and a probe at the top. The display shows '24.1'. The text 'UNI-T UT311' is visible on the device.
121	UT312	UT312 UNI-T Portable LCD Vibration Analyzer Tester Meter (split style)	6935750531204	5	 The image shows a red and black handheld vibration analyzer with a split-style design. It has a digital display showing '24.1' and a probe connected by a coiled cable. The text 'UNI-T UT312 PORTABLE VIBROMETER' is visible on the device.
122	UT315A	UT315A UNI-T Digital Vibration Tester, can measure displacement, velocity, and acceleration of rotating and reciprocating machinery, Acceleration (O-P) Frequency response: 10Hz-10kHz, Velocity (RMS)Frequency response: 10Hz-1kHz, Displacement (P-P)Frequency response: 10Hz-500Hz and USB interface.	6935750531518	1	 The image shows a red and black digital vibration tester. It has a large digital display showing '0.00' and a probe connected by a cable. The text 'UNI-T UT315A' and 'CE USB' are visible on the device.




S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
123	UT343D	UT343D UNI-T Coating Thickness Gauge (ferrous and non-ferrous materials). This CE certified device can store up to 500 sets of data for further analysis through the PC analytical software that is included. It is widely used in manufacturing, metal processing, aerospace, marine mechanics, rail transport, scientific research, quality supervision, and other industries.	6935750534304	10	
124	UT371	UT371 UNI-T Non Contact Optical Digital Tachometer	6935750537107	10	
125	UT372	UT372 UNI-T Digital Non Contact Tachometer with USB interface	6935750537206	10	
126	UT373	UT373 UNI-T Mini Digital Non Contact Tachometer	6935750537305	20	






S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
127	UT377A	UT377A UNI-T Digital Wood Moisture Hygrometer (2% - 40%)	6935750537718	20	
128	UT382	UT382 UNI-T Digital Lux Meter with USB interface	6935750538203	10	
129	UT383	UT383 UNI-T Digital Mini Lux Meter	6935750538302	40	
130	UT383BT	UT383BT UNI-T Digital Mini Lux Meter with Bluetooth (UT383BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store, or UNI-T's website by searching 'iENV'.)	6935750538319	20	
131	UT383S	UT383S UNI-T Digital Lux Meter with separate sensor probe	6935750538326	40	




S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
132	UT387A	UT387A UNI-T Digital Wall Scanner (for Stud & Thick Scanning)	6935750538715	20	
133	UT387B	UT387B UNI-T Digital Wall Scanner, SCAN behind walls - metals, live electrical wires, and wood	6935750538722	10	
134	UT387C	UT387C UNI-T Wall Scanner, Electro-magnetic induction to Detects-Wooden beam, metal object, electric wire, Calibration error alarm and Notification-LED/buzzer etc..	6935750538760	20	
135	UT387D	UT387D Wall Scanner, Electro-magnetic induction to Detects-Wooden beam, metal object, electric wire, Notification-Voice etc..	6935750538753	20	
136	UT665	UT665 UNI-T Borescope, displays clear images through a flexible camera probe (IP67 probe 1M water proof, TFT screen type)	6935750566503	8	





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
137	UT658B	UT658B UNI-T Digital USB Tester with wire	6935750565827	60	
138	UT658LOAD	UT658LOAD UNI-T Digital USB Tester, Input & Output ports (Type A), Electrical load 0.5A, 1A, 2A, 3A (Max power: 60W), QC 3.0 fast charge protocol, it can inspect USBchargers, portable power sources, it can measures output voltage,current, energy, capacity, circuit equivalent resistance, D+ andD- voltages of USB data cables etc..	6935750565100	60	
139	UT681C	UT681C UNI-T Portable Cable Line Detector (RJ 45/RJ 11) with BNC Adaptor	6935750568118	40	
140	UT681HDMI	UT681 HDMI UNI-T HDMI/MINI HDMI Data Cable Tester (For HDMI & Mini HDMI)	6935750568125	40	
141	UT681L	UT681L UNI-T Cable Connection Tester (RJ 45/RJ 11)	6935750568132	40	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
142	UT682	UT682 UNI-T Wire Tracker for LAN cable, Tel. Line, Coaxial Cable & Electrical wire	6935750568255	20	
143	UT682D	UT682D UNI-T Wire Tracker for Tel. Line, Twisted Pair & Electrical wire	6935750568262	20	
144	UT501A	UT501A UNI-T Digital Insulation Resistance Tester (From 100V to 1000V)	6935750550113	20	
145	UT502A	UT502A Insulation Resistance Tester (Test Voltage from 500V to 2500V)	6935750550212		
146	UT501C	UT501C Insulation Resistance Tester, new design, large scale integrated circuit and digital circuit, are utilized to measure insulation resistance, alternating voltage and other parameters. high accuracy, stable performances, comfortable and reliable operation. Insulation Resistance from 100V to 1000V.			

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
147	UT505A	UT505A Digital Handheld true RMS Insulation Resistance Tester, Insulation resistance up to 20G-1000V, Load current-1mA, Auto range, DAR, PI/Timing Measurement, Auto discharge, Analogue bar graph, Continuity, Comparison measurement and features of a digital multimeter-AC-DC voltage etc..	6935750550519	5	
148	UT511	UT511 UNI-T Digital Insulation Resistance Tester with DC voltage AC Voltage & resistance, Test Voltages100V~1000V	6935750551103	4	
149	UT512	UT512 UNI-T Digital Hi End Insulation Resistance Tester Test Voltages from 500V to 2500V)	6935750551202	4	
150	UT513A	UT513A UNI-T Digital Hi End Insulation Resistance Tester Test Voltages from 500V to 5000V)	6935750505137	4	





S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
151	UT521	UT521 UNI-T Digital Earth Ground Tester upto 2000 Ohms & 200V with frequency	6935750552100	8	
152	UT522	UT522 UNI-T Digital Earth Ground Tester, 4000count, 4000 Ohms & 400V with Frequency	6935750552209	8	
153	UT526	UT526 UNI-T multifunctional electrical installation tester -insulation resistance, RCD status, low resistance, continuity, and voltage measurement (upto 500 mega Ohms & Test voltages 250V/500V/1000V)	6935750552605	10	
154	UT582+	UT582+ UNI-T Digital RCD (ELCB) Tester, 1000 count with phase switch, connections check, AUTO RAMP, disconnect buzzer, over-range display	6935750558218	5	
155	UT595	UT595 UNI-T Multifunction Installation Tester, 9999-count LCD display with analogue bar, 250V-1000V DC insulation resistance test, 200mA earth-resistance continuity test, Loop impedance/Prospective Fault Current (PFC)/Prospective Short Current (PSC) test, Lock test, RCD trip time test and the data storage with one key, Full/Half wave and count downing (30s) test mode selectable, 0/180 phase angle option to detect the fastest trigger time, Trip current test of RCD trip time X2, RCD trip trigger current test, Phase sequence and missing test, AC/DC voltage auto check and test, Connection check with status real-time display etc..	6935750559505	1	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
156	UT705	<p>UT705 UNI-T Single Function Loop Calibrator, high-accuracy DC current and transmitter analog current outputs, Measures: DC voltage, DC current, 4-20mA loop current, Output functions: DC current, analog transmitter, 24V loop, Up to 0.02% accuracy current measurement at the same time, Automatic ramp for DC current output, Manual stepping and automatic stepping and ramping output, Stores and recalls setups, LCD backlight, auto power off and 1m drop proof etc..</p>	6935750570180	5	
157	UT673A	<p>UT673A UNI-T Battery Tester, analyze the battery health of automobile batteries, suitable for battery capacities from 30Ah to 200Ah. CE certified, can rapidly and accurately detect common faults caused by battery. 12V cranking lead acid battery test, 12/24V charging or cranking system test, Display battery capacity, voltage, resistance and life, Four-terminal Kelvin test, 10 types of battery standards, LED color indication for test result</p>		30	
158	UT675A	<p>UT675A UNI-T Battery Tester can be used to analyze the battery health of automobile batteries, suitable for battery capacities from 30 to 250Ah. These CE certified testers can rapidly and accurately detect common faults caused by battery. UT675A also includes USB communication and built-in printer for report generation. 12V cranking lead acid battery test, 12/24V charging or cranking system test, Display battery capacity, voltage, resistance and life. Four-terminal Kelvin test. 10 types of battery standards. Language option (Chinese/English). Test without battery disassembly.</p>	6935750567500	10	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
159	UTD1025CL	UTD1025CL UNI-T Handheld Digital Storage Oscilloscope with the functions of oscilloscope and multimeter, ergonomic, lightweight, universal instruments, Bandwidth 25MHz, 1 Channel, Sampling rate 250MS/s, Mini USB interface, AC-DC V, AC-DC A, Ohm, Capacitance, 4000count, 3.5 inches 64k TFT LCD, 320 x 240 etc..	6935750590089	2	
160	UTP1306	UTP1306 UNI-T Switching DC Power Supply, Single output, Output: 32V, 6A, Resolution: 10mV/1mA, Over voltage/current protection, 3 groups of one-key recall of stored datas, Over current/voltage protection value settable, Independent output switch, 192W output power, LED voltage and current dual display, EBTN LCD, Input voltage: 110V AC/220V AC, 50Hz-60Hz etc..	6935750513385	6	
Temperature and Humidity Meter (Thermo Meter / Hygro Thermo Meter)					
1	NT9282A	NT9282A - NEWTON Pocket type LCD Digital Thermometer (-50 to +300C), On/Off, Hold/Test, F/C Functions, 97mm Stainless Steel Sensor Probe, One hour Auto Shut Off Function (Blister Packing)	5553790019257	25 / 50	
2	VT9222A	VT9222A - Voltron Pocket type Multi Digital Thermometer (-50 to +300C), On/Off, Hold/Test, F/C Functions, Foldable 97mm Stainless Steel Sensor Probe, One hour Auto Shut Off Function (Blister Packing)	5553790019233	25 / 50	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
3	VT9348B	VT9348B - Voltron Pocket type Foldable Waterproof Digital Thermometer (-50 to +300C), On/Off, F/C Functions, Dia 2 x 89mm Stainless Steel Robust Sensor Probe, One hour Auto Shut Off Function (Blister Packing)	5553790019349	25 / 50	
4	VT9283B	VT9283B - Voltron Pocket type Portable Digital Thermometer (-50 to +300C), On/Off, F/C, Hi/Low Alarm Functions, 133mm Stainless Steel Sensor Probe with 1M Black sensor wire, One hour Auto Shut Off Function (Blister Packing)	5553790019288	25 / 50	
5	VHT9222	VHT9222 - Voltron Indoor/Outdoor LCD Digital Hygro Thermometer (-50 to +70C), On/Off, F/C, Max-Min, Temp. & Humidity memory recalling, Comfortable and Uncomfortable index, 3M white sensor wire with sensor probe (Blister Packing)	5553790019240	10 / 20	
Test and Measuring Instruments list					
1	VDMM70 (DT700C)	(DT700C) VDMM70 Palm size Digital Multimeter, 1000V DC, 750V AC, 10A DCA, Ohm, Diode, Temp, Transistor test and Continuity	0	100	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
2	VDMM60 (MY60)	(MY60) VDMM60 Standard Digital Multimeter AC-DC V, 10A AC-DC, Ohm, Diode, Transistor test and Continuity	0	20	
3	VDMM30 (A830L)	(A830L) VDMM30 Standard Digital Multimeter, 600V AC-DC, 10A DCA, Ohm, Diode, hFE Transistor test, 1.5V Battery Test, Backlight and Continuity	0	50	
4	VDCM66 (266)	(266) VDCM66 Standard Digital Clamp meter 1000A AC, AC-DC V, Ohm and Continuity	0	40	
5	VDCM67 (MT87)	(MT87) VDCM67 Pocket size mini Digital Clamp meter 400A AC, AC-DC V, Ohm, Diode test and Continuity	0	100	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
6	VDCM21 (DT203)	(DT203) VDCM21 Standard Digital Clamp meter 600A AC, AC-DC V, Ohm, Temp, Diode, Capacitance, Hz, and Continuity	0	50	
7	VDCM22 (DT203B)	(DT203B) VDCM22 Standard Digital Clamp meter 600A AC-DC, AC-DC V, Ohm, Diode, Capacitance, Hz, and Continuity	0	50	
8	VDCM23 (DT2015C)	(DT2015C) VDCM23 Standard Digital Clamp meter 600A AC, AC-DC V, Ohm, Diode, Capacitance, Hz, Continuity, True RMS, Flash Light and NCV	0	20	
9	VVT81 (8in1)	(8in1) VVT81 AC-DC auto detection two pole voltage tester (6V to 400V), IP54 design and Polarity test - Positive or Negative	0	100	

S.NO.	Model NO.	Item Description	Bar Code	Ctn. Packing	Product Picture
10	VAMMYX365 (KH965)	(KH965) VAMMYX365 Standard Analogue Multimeter, 1000V AC-DC, ACA-DCA, Continuity Buzzer, Ohm, dB, Capacitance, Load current (LI), Load Voltage (LV) and HFE Transistor etc..	0	40	