

815V

Brass Foot Valve



Via Circonvallazione, 10
13018 Valduggia (VC), Italy
Tel: +39 0163 47891
Fax: +39 0163 47895
www.vironline.com



Brass foot valve
Female threaded (ISO 228/1)
SBR seal
To be installed vertically (with upward flow)
TR CU 010 compliant

DN15/25	DN32/50	DN65/150
PN10	PN8	PN6

Free of CE marking (cat. according to Art. 4.3 Dir. 2014/68/EU)

Working conditions

- Suitable for: water, 0°C to +90°C
- Not suitable for: gases group 1 & 2, liquids group 1 (Dir. 2014/68/UE)

PARTLIST

N.	Part	Material	Norm
1	Strainer	Brass	EN12165 CW617N
2	Gasket	Fiber	-
3	Disc gasket	SBR	-
4	Disc	Brass	EN12165 CW617N
5	Body	Brass	EN12165 CW617N

DIMENSIONS

DN	G	H [mm]	A [mm]	Weight [g]
015	1/2"	60	39	115
020	3/4"	73	45	213
025	1"	81	51	285
032	1 1/4"	95	61	408
040	1 1/2"	103	68	578
050	2"	121	80	830
065	2 1/2"	136	103	1300
080	3"	151	115	1800
100	4"	187	145	3075
150	5"	238	180	5000
100	6"	267	201	7000



ERC

