

GD Floor Standing



Powerful Airflow

Equipped with a powerful DC motor and a large-diameter centrifugal blower wheel to achieve an airflow up to 2300m³/h.



15 Meters Long Distance Wind Blast

The large air outlet and six large air directing blades enable an airflow distance of up to 15m.



Hidden VLED Display

The hidden VLED display screen is easy to read yet beautiful.



Wind Avoid Me

With one tap of button, the airflow direction is automatically adjusted to the maximum angle to prevent direct cold/hot drafts.



Touch Control

The control buttons are embedded into the body so that the unit can be controlled within just a simple touch.



3D Airflow

Midea's 3D airflow function combines vertical and horizontal auto-swing to spread comfort more widely throughout the room.



Floor Standing



Floor Standing

Model Name	Indoor	CFTGA-36CRNI-QC1W	CFT4GA-48CRNI-RC1W	CFT4GA-55CRNI-RC5W
	Outdoor	COTDUL-36CRNI-QC1W	COT4DUL-48CRNI-RC1W	COT4EUL-55CRNI-RC5W
Capacity (Btu/h)	Cooling	T133000	T148000	T154000
	Heating	T329200	T343000	T348000
Power input (W)	Cooling	T12980	T14400	T14520
	Heating	T33500	T35350	T35550
EER (Btu/h)/W	Cooling	T11107	T11091	T11195
	Heating	T3834	T3804	T3865
COP (W/W)	Cooling	-	-	-
	Heating	T11322	T1850	T1800
Rated Current (A)	Cooling	T31542	T3950	T3932
	Heating	-	-	-
Power supply (Ph/V/Hz)	/	1/220-240/50	3/380-415/50	3/380-415/50
Indoor air flow (m³/h) (Turbo/H/Lo)	/	2040/1910/1650	2396/2280/1840	2280/2050/1950
Refrigerant	/	R410A	R410A	R410A
Indoor				
Net dimension (mm)	W*D*H	610x390x1925	610x390x1925	610x390x1925
Packing dimension (mm)	W*D*H	765x515x2070	765x515x2070	765x515x2070
Net/Gross weight (kg)	/	555/737	572/757	567/761
Indoor noise level[dB(A)](Turbo/H/Lo)	/	53/51/44	58/57/51	57/54/53
Outdoor				
Net dimension (mm)	W*D*H	946x410x810	900x350x1170	952x415x1333
Packing dimension (mm)	W*D*H	1090x500x875	1032x443x1307	1095x495x1480
Net/Gross weight (kg)	/	724/769	896/100	1126/1266
Outdoor noise level [dB(A)]	/	62	62	61
Refrigerant piping				
Liquid side/ Gas side	mm(inch)	Ø95.2(Ø19.3/87.3/4")	Ø95.2(Ø19.3/87.3/4")	Ø95.2(Ø21.3/87.7/8")
Max. pipe length	m	30	50	50
Max. difference in level	m	20	30	30

NOTES:
 T1: Outdoor: 35CD8 - Indoor: 27CD8/15CV8
 T3: Outdoor: 46CD8 - Indoor: 29CD8/15CV8