



Material Safety Data Sheet

1 .PRODUCT IDENTIFICATION

Product Name: DEVCON HOME CONTACT CEMENT Product Type: Adhesive

This product appears in the following stock number(s):
18045

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component:	Weight%	ACGIH; TLV-TWA	OSHA PEL
ACETONE 67-64-1	20-40	500 ppm	1000 ppm; 2400 mg/m ³
ETHYL ACETATE 141-78-6	20-40	400 ppm	400 ppm; 1400 mg/m ³
HEPTANE 142-82-5	20-40	400 ppm	500 ppm; 2000 mg/m ³

3 . HAZARDS IDENTIFICATION

Toxicity: This material is irritating to skin, eyes and respiratory tract. The solvent(s) listed have been reported to affect the central nervous system. Ethyl acetate may cause anemia.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Ingestion may

cause nausea and vomiting. Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Repeated exposure may cause skin dryness or cracking.

Component:	Weight%	NTP	ACGIH Carcinogens	IARC Carcinogen
ACETONE 67-64-1	20-40		A4 - Not Classifiable as a Human Carcinogen	

Aggravated Medical Condition: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4 . FIRST AID MEASURES

Ingestion: If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists

5 . FIRE FIGHTING MEASURES

Flash Point °F(C°): -4 °F (-20°C)

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact

Hazardous Products of Combustion: Oxides of carbon

Unusual Fire/Explosion Hazards: Danger! This product is extremely flammable. May cause flash fire. Heated cans may burst.

Lower Explosive Limit: 1.9 %

Upper Explosive Limit: 12.8 %

6 . ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7 . HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).

Handling: Danger: Extremely flammable. Do not use near heat, sparks or open flame. Keep containers tightly closed when not in use. Avoid contact with skin and eyes. Use in a well ventilated area. Wash thoroughly after handling.

8 . EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses
Skin: Neoprene or nitrile gloves recommended
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits

9 . PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber liquid
Odor: Solvent
Boiling Point: 132 °F (55°C)
Solubility in Water: Insoluble
pH: Not applicable
Specific Gravity: 0.84
VOC(Wt.%): 52.7 %
Vapor Pressure: Not Determined
Vapor Density (Air=1): >1
Evaporation Rate: >1 (butyl acetate = 1)

10 . STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Strong oxidizers, Strong bases, Strong alkalis, Acids
Conditions to Avoid: Keep away from heat, sparks and open flame. - No smoking **Hazardous Products of Combustion:** Oxides of carbon

11 . TOXICOLOGICAL INFORMATION

See Section 3

12 . ECOLOGICAL INFORMATION

No data available

13 . DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations
US EPA Waste Number: D001 as per 40CFR 261.21

14 . TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Adhesives, Limited Quantity
Hazard Class: Class 3, PG II
UN/ID Number: UN 1133

IATA (Air)

Proper Shipping Name: Consumer Commodity
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG (Vessel)

Proper Shipping Name: Adhesives, Limited Quantity
Hazard Class: Class 3, PG II
UN Number: UN 1133

15 . REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

None

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16 . OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 0

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)



For More Information, Please Contact:

Deira Dubai

Phone: 04 336 1377

Al Qouz

Phone: 04 338 7577

Email:

info@anbisolutions.com

websales@anbisolutions.com