

UT203+ 400A digital clamp meter

1. Industrial electricity 2. Residential electricity 3. Air conditioning 4. Automobile

Specifications	Range	UT203+
AC current (A)	400A	$\pm(2.5\%+5)$
DC current (A)	400A	$\pm(2.5\%+5)$
AC voltage (V)	600V	$\pm(0.8\%+5)$
	10Hz~60kHz	$\pm(0.5\%+2)$
DC voltage (A)	600V	$\pm(0.5\%+2)$
Resistance (Ω)	40M Ω	$\pm(0.8\%+2)$
	40mF	$\pm(4\%+5)$
Frequency (Hz)	10Hz~10MHz	$\pm(0.1\%+4)$
Features		
Display count		4000
Auto range		√
Jaw opening		28mm
True RMS		√
NCV		√
Continuity test		√
Diode		√
MAX/MIN		√
Relative mode		√
Zero mode		√
Data hold		√
Low battery indication		√
Auto power off		√
Power	1.5V battery (R03) x 2	
Display	37mm x 25mm	
Product color / net weight / size	Red and grey / 235g / 215mm x 63mm x 36mm	
Standard individual packing	Gift box, Carring bag, English manual	
Standard quantity per carton	40pcs / measurement - 485mm x 295mm x 385mm	
Standard carton gross weight	16.8kg	