




Design & Quality ANBI-Italy

## TECHNICAL SPECS

MODEL# ABB-251-CP



## BEN SERIES

**MODEL# ABB-251-CP**

mono sink mixer with swivel spout

- > Mono Sink Mixer
- > with tubular swivel spout
- > with water flow straightener
- > ceramic cartridge
- > 2NOS x 1/2" Nut x 300mm Flexible Pipe Connectors
- > Deck Mounted Drill Hole diameter 28mm
- > Minimum Operating Pressure 0.3Bar LP
- > Chrome finish




Design & Quality ANBI-Italy

# TECHNICAL SPECS

MODEL# ABB-251-CP

## dimensions





Design & Quality ANBI-Italy

# TECHNICAL SPECS

MODEL# ABB-251-CP

## important - please read

Please read these instructions carefully before starting installation and keep for future reference.

Remove all packaging and check the product for missing parts or damage before starting installation.

Any alterations made to this product and fittings may infringe water regulations and will invalidate the guarantee.

The installation must comply with all Local/National Water Supply Authority Regulations/Byelaws and Building and Plumbing (UK:BS6700) Regulations.

We strongly recommend that you use a qualified and registered plumber.

## general installation

These fittings are mixing devices and therefore water supplies must be reasonably balanced.

Where connections are made to the mains cold water supply, WRC approved single check valves must be fitted to both hot and cold inlets. This is a stated requirement of Water Supply (Water Fittings) Regulations 1999 Schedule 2, Section 6 G15.13.2

Before making any inlet pipe connections, all supply pipes MUST be thoroughly flushed to remove debris. Failure to do so could result in damage or low flow from the mixer unit. Water Supply (Water Fittings) Regulations 1999 Schedule 2 Section 4 G13.1

The fitting of isolating valves to the inlet feeds is advised for ease of maintenance.

Please take great care when installing this mixer not to damage its surface.

Please note if installing in an enclosed environment, access should be left for servicing and maintenance. No costs relating to inadequate access can be accepted.

## care of the mixer

Our products are finished to the highest standard and due care needs to be taken to ensure their looks are retained.

We recommend cleaning all products with a soft damp cloth ONLY and advise strongly against the use of ALL cleaning products i.e. powders and liquids.

If the above instructions are not followed this will invalidate your guarantee in the event of a problem occurring.




Design & Quality ANBI-Italy

## TECHNICAL SPECS

MODEL# ABB-251-CP

### operation



Turn the handles anti-clockwise to increase the flow of water and clockwise to decrease the flow.

### Operating Specifications

Operating Pressure:  
Minimum operating pressure 0.3 bar  
Maximum operating pressure 5 bar



Design & Quality ANBI-Italy

# TECHNICAL SPECS

MODEL# ABB-251-CP

## installation

### Assembly the spout to the body.

Push the spout down into body and tighten the nut.

### Installation.

Before installing your new mixer, flush through the pipework to ensure removal of debris, turn off the water supply.

Screw the two flexible pipes to the mixer body, tighten using the correct size spanner, but do not over tighten.



Screw the threaded rod into the front hole in the base of the mixer body.

Ensure the rubber base ring is in place in the base of the mixer.

Position the mixer on the basin. From the underside of the basin fit the rubber washer onto the threaded rod followed by the metal washer and the nut. Tighten the nut to clamp the mixer to the basin.

**CAUTION:** Do not over tighten the nut as this may damage the basin.

Connect the water supply to the inlet pipes. The hot water should be connected to the left hand pipe.





Design & Quality ANBI-Italy

# TECHNICAL SPECS

MODEL# ABB-251-CP

## customer/technical services

For any technical or installation queries please contact your local dealer or email us on [info@anbisolutions.com](mailto:info@anbisolutions.com)

## guarantee

This product is guaranteed against manufacturing defects from the date of purchase until the expiry of the relevant guarantee period shown below.

The guarantee is only valid if:-

1. The product has been installed, used and maintained in accordance with ANBI instructions and subjected to normal use only.
2. The defect is not due to use of an unsuitable or inadequate water or power supply.
3. The defect is not due to accident, misuse; neglect or repair other than by ANBI or ANBI authorized agents or damage caused by foreign objects or substances.
4. We have received from you the completed Guarantee Registration Form. ANBI accepts no responsibility for any forms lost in the post and returns by registered means is therefore recommended.

Under this guarantee (which is non-transferable) ANBI will, at its option, repair or replace free of charge any product (or replacement part) found to be defective. The guarantee does not extend to any consequential loss or damage. After repair or replacement the relevant guarantee period will be calculated from the original date of purchase.

The relevant guarantee periods are:-

1. Two years on all other products.

All claims under the guarantee must be submitted in writing to the person who supplied the product to you and must be received no later than the last day of the relevant guarantee period. All claims must be accompanied by proof of purchase (sales receipt or delivery note).

ANBI operates a policy of continuous product development and therefore reserves the right to change the product, packaging and documentation specifications without notice.

This guarantee is in addition to and does not affect your statutory rights as a consumer.